



1					2					3					4				
d ₁	d ₂	l ₁			d ₃	d ₄	d ₅	h ₁	h ₂	l ₂	l ₃	l ₄							
32	M 6	25	35	45	15	14	4,5 ±0,03	20	10	5,1	3,6	7,6							
40	M 8	30	40	50	18	18	6,1 ±0,05	25	13	6,2	4,2	9,2							
40	M 8	30	40	50	21	18	6,1 ±0,05	25	13	6,2	5	10							
40	M 8	30	40	50	25	18	6,1 ±0,05	25	13	6,2	5,5	10,5							
40	M 8	30	40	50	32	18	6,1 ±0,05	25	13	6,2	6	11							
40	M 8	30	40	50	40	18	6,1 ±0,05	25	13	6,2	8	13							
50	M 10	35	45	55	21	22	7,8 ±0,05	32	17	7,3	4,3	10							
50	M 10	35	45	55	25	22	7,8 ±0,05	32	17	7,3	4,6	10,5							
50	M 10	35	45	55	32	22	7,8 ±0,05	32	17	7,3	5	11							
50	M 10	35	45	55	40	22	7,8 ±0,05	32	17	7,3	7	13							

Specification

- Star knob DIN 6336
Plastic
Technopolymer (Polyamide PA)
black, matt
- Threaded stud
Stainless Steel AISI 304 Cu
- Thrust pad
Plastic
Technopolymer (Polyacetal POM)
- temperature resistant up to 80 °C
- black, matt
- Plastic characteristics → Page 1141
- Stainless Steel characteristics → Page 1144
- RoHS compliant

Information

Star knobs GN 6336.11 / GN 6336.12 have a ball pin whose diameter is smaller than the core diameter of the thread.

The movable thrust pad is easily clipped on and taken off.

The thrust pads are supplied disassembled.

see also...

- Ball jointed levelling feet GN 638 (without star knob) → Page 816
- Knurled thumb screws GN 421.11 / GN 421.12 → Page 320

Star knobs with ball pin		1	d ₁
GN 6336.11-40-M8-50		2	d ₂
		3	l ₁

Star knobs with movable thrust pad		1	d ₁
GN 6336.12-50-M10-45-25		2	d ₂
		3	l ₁
		4	d ₃